trace **ID**

TE14 Thinpropeller

^{*}

UHF RFID Inlays

GENERAL CHARACTERISTICS:

Operating Frequency: Global (860 - 960MHz) RF Protocol: ISO-18000-6C, EPC Class 1, Gen 2 Chip: IMPINJ Monza 4D/E/QT EPC Memory: 128/496/128 bits USER Memory: 32/128/512 bits

TID Memory: 96 bit, pre- encoded for multi- vendor chip (MCS) based serialization, factory programmed

COMMON APPLICATIONS:

- Supply chain, inventory and logistics
- Apparel and other item-level retail
- Returnable Transport Units (RTU)

FORMAT	DRY INLAY	WET / WHITE WET INLAY
Antenna dimensions (Width x Length)	95 x 8mm [3.74 x 0.51 in]	95 x 8mm [3.74 x 0.51 in]
Die- cut dimensions	N/ A	97 x 12mm [3.82 x 0.47 in]
Inlay substrate material	PET	PET
Inlay- to- liner adhesive	N/ A	RC15 (UPM)
Liner material	N/ A	Honey Glassine 65 (UPM)
Face sheet	N/ A	White or clear Polypropylene / Vellum paper
Standard pitch	16.42mm [0.65 in]	16.42mm [0.65 in]
Standard web width	110mm [4.33 in]	104mm [4.09 in]
Total thickness over chip	177.8 - 203.2 microns	254 - 330.2 microns
Operating temperature	-40 to 85° C [-40 to 185°F]	-40 to 85° C [-40 to 185°F]
RoHS	EU Directive 2011/65 EU Compliant	EU Directive 2011/65 EU Compliant
Quality assurance	100% read tested with out- of- tolerance inlay marked	100% read tested with out- of- tolerance inlay marked
Un- wind direction	Inlay- side Out	Label side out
Core size with adaptor insert	152.4mm [6 in]	76.2 mm [3 in]
Maximum roll outer diameter (not to exceed)	431.8mm [17 in]	304.8mm [12 in]
Average # of units per roll	тво	тво

Minimum order quantity for customized labels, tickets, care labels (textile labels):

CARE AND HANDLING RFID inlays are sensitive to ESD. Observe standard practices to keep environmental static charge to a minimum.

APPLICATIONS This product should be tested by the customer/ user thoroughly under end use conditions to ensure the product meets the particular requirements. Trace-ID does not represent that this product is fit for any particular purpose or use.

PRODUCT CHANGES Trace-ID reserves the right to modify, change, supplement or discontinue product offerings at any time without notice.

© 2016 Trace-tech Id Solutions S.L. All rights reserved.

TRACE-TECH ID SOLUTIONS S.L. Tel: +34 932 606 527

c/ Riera dels Frares nº5-7 08907 VAT number: ESB 65324162

Hospitalet del Llobregat (Barcelona) – SPAIN www.trace-id.com - info@trace-id.com

10.000 pcs